

IN THE CLAIMS:

Kindly cancel Claims 1-8 and 18-27 (renumbered as 15-24) drawn to an apparatus of roofing layers, classified in class 52, subclass 408.

Please amend claims 10-14, as follows:

10. (original and renumbered) A method of installing fire resistant roofing tiles comprising:

- a) spraying a foam rising adhesive on a surface;
- b) waiting for said foam rising adhesive to obtain a creamy consistency;
- c) applying a first tile panel and an adjacent first subsequent tile panel to said surface; each said tile panel having a respective fire resistant layer adhered thereto;
- d) waiting for said adhesive to cure and rise within a joint formed between said first tile panel and said first subsequent tile panel;
- e) applying further tile panel and subsequent further tile panel to said surface;
- f) waiting for said adhesive to cure and rise within further joints formed between said first subsequent tile and said further tile panel;
- g) repeating steps "c", "d" and "e" and "f" on next subsequent pairs of tile panels until said foam adhesive completes rising between said joints and accumulates as debris above a plane formed by said tile panels accumulated in a seamless configuration;
- h) removing debris formed by said foam rising adhesive from the top surface of said tile panels; and,
- i) applying an elastomeric coat to the top surface of said joined, seamless accumulation of tile panels.

11. (currently amended and renumbered) A method of installing roofing tiles according to claim ~~13~~ 10, wherein said elastomer is an acrylic.

12. (currently amended and renumbered) A method of installing roofing tiles according to claim ~~14~~ 10, wherein said elastomer is a urethane.

13. (currently amended and renumbered) A method of installing roofing tiles according to claim ~~13~~ 10, wherein said elastomer is silicone based.

14. (currently amended and renumbered) A method of installing roofing tile panels according to claim ~~14~~ 11, wherein application of said first and said subsequent tile panels further comprises:

applying said first tile panel having a first length;
and

applying said second tile panel having a second length,
wherein said second length of said second tile panel is
different than said first length of said first tile panel.